



OVERVIEW

In its simplest form yet with maintained functionality, EcoSUND® Industry allows for easy installation, quickly covering larger areas on walls or in integrated solutions. Standard sizes in fixed formats suit most situations, with a heated surface. Choose the color of the core material. The absorbent, with a pre-drilled pattern for a washer and screw, provides the possibility for straightforward installation.

FORMAT AND MATERIALS

EcoSUND® INDUSTRY manufactured in three standard formats: 1200x600mm, 1200x1200mm, and 2400x1200mm. All absorbers are 50 mm thick for effective sound absorption.

ECOSUND

Choose the color of the core material. When choosing an absorbent with a straight cut edge where the core material Ecosund is visible from the side. Keep in mind that black core material affects the appearance of a light textile.



White



Black



Grey



Light Grey

PRESCRIPTION

AM Acoustics EcoSUND® INDUSTRY wall absorbents. Core material Ecosund®. Mounting: without attachment, hook and loop, or screw. Total thickness: 50 mm. Formats: 1200x600mm, 1200x1200mm, and 2400x1200mm.

FIRE

With standard fabrics EcoSUND® INDUSTRY has been rated B-s1,d0.

MOUNTING

EcoSUND® INDUSTRY to be mounted with own attachment, Velcro, or alternatively washer and screw.

VARIANTS

Format

600x1200x50
1200x1200x50
1200x2400x50
600x1200x50
1200x1200x50
1200x2400x50